

Amendment to the Claims

Please amend the claims as indicated in the attached listing of claims. This listing replaces all prior listing of claims.

1. (Currently Amended) A method for providing proxy services in a network of modules included in a work machine environment, the method performed by a gateway and comprising:

detecting a first message sent by a source module on a first data link, wherein the first message is directed to a destination module and includes an address identifier corresponding to the destination module;

retrieving the first message and extracting the destination address identifier from the message;

routing, based on the destination address and an address map, the first message to a proxy logic element that performs functions associated with the destination module based on data included in the first message.

2. (Previously Presented) The method of claim 1, wherein detecting a first message on a first data link comprises detecting a first message sent by a source module on a proprietary data link.

3. (Previously Presented) The method of claim 1, further comprising:
providing the first message from the proxy logic element to a second module over a second data link interfaced by the proxy logic element.

4. (Previously Presented) The method of claim 3, further comprising:
receiving a second message responsive to the first message from the
second module via the second data link; and
routing the second message to the first module over the first data link via
the address map.

5. (Previously Presented) The method of claim 4, further comprising:
detecting that the first data link is incompatible with the second data link;
and
translating the second message into a comparable message consistent
with the first data link.

6. (Previously Presented) The method of claim 1, further comprising:
generating, by the proxy logic element, a second message that is
responsive to the first message and routing the second message to the source module
via the first data link.

7. (Canceled).

8. (Currently Amended) A method for providing proxy services in a
network of modules included in a work machine environment, the method performed by
a gateway and comprising:

monitoring a first data link for messages, wherein the messages are transmitted by source nodes and intended for destination modules;

determining whether a first message intended for a first destination module should be intercepted from the first data link based on a destination address included in the first message;

intercepting the first message when the gateway determines that the message should be intercepted; and

routing, based on information in an address map, the first message to a proxy logic element that performs functions associated with the first destination module based on data included in the first message.

9. (Previously Presented) The method of claim 8, wherein the source nodes include at least one of either an on-board module and an off-board system.

10. (Currently Amended) A proxy control module in a work machine, the proxy module comprising:

means for monitoring a first data link connected to a plurality of modules, each module configured to direct messages to destination modules by adding to the messages an address identifier corresponding to the destination modules;

means for intercepting at least one of the messages based on a determination that the at least one message is intended for a destination module for which the gateway serves as a proxy; and

means for selectively providing, using an address map, the at least one message to program logic that performs, based on data included in the at least one message, work machine control functions similar to the destination module that may be connected to the first data link to perform the same functions.

11. (Currently Amended) A proxy control module in a work machine, the proxy module comprising:

means for monitoring a first data link connected to a plurality of modules, each module configured to direct messages to destination modules by adding to the messages an address identifier corresponding to the destination modules;

means for determining whether the messages include respective address identifiers that correspond to address identifiers included in an address map;

means for intercepting at least one of the messages based on a determination that the at least one message includes an address identifier that corresponds to an address identifier in the address map; and

means for selectively providing, using an address map, the at least one message to program logic that performs, based on data included in the at least one message, work machine control functions similar to a destination module that may be connected to the first data link to perform the same functions.

12. (Currently Amended) A system for exchanging information in a work machine environment having a network of modules, the system comprising:

a source module for broadcasting a first message over a first data link that uses a first protocol, wherein the first message is intended for a destination module and includes a destination address identifier associated with the destination module; and

a gateway coupled to the first data link and configured to:

monitor the first data link for messages,

intercept the first message from the first data link based on a determination that the destination address corresponds to proxy logic included in the gateway, and

route the intercepted message, based on information in an address map, to the proxy logic, wherein the proxy logic performs functions associated with the destination module based on data included in the intercepted message.

13. (Previously Presented) The system of claim 12, wherein the first data link is a proprietary data link.

14. (Previously Presented) The system of claim 12, further comprising a second data link that interfaces the proxy logic element.

15. (Previously Presented) The system of claim 14, wherein the gateway is further configured to transmit information responsive to the first message from the proxy logic element over the second data link.

16. (Previously Presented) The system of claim 14, wherein the gateway is further configured to receive a second message from the second data link and route, using the address map, the second message over the first data link to the source module.

17. (Previously Presented) The system of claim 16, wherein the second data link is a non-proprietary standard data link including one of J1939, CAN, MODBUS, serial standard data link, and the Ethernet.

18. (Previously Presented) The system of claim 17, wherein the gateway is further configured to translate the second message into a comparable message consistent with the first data link.

19. (Currently Amended) A system for exchanging information in a work machine environment having a network of modules, the system comprising:
a source module for broadcasting a first message over a first data link that uses a first protocol, wherein the first message is intended for a destination module and includes a destination address identifier associated with the destination module; and

a gateway coupled to the first data link and configured to:

monitor the first data link for messages,

retrieve the first message from the first data link,

extract the destination address identifier from the first message,

search an address map for the destination address included in the first message,

and

when the destination address is found in the address map, route, based on information in the address map, the first message to a proxy logic element that performs functions associated with the destination module based on data included in the first message, wherein the proxy logic element is located in the gateway.

20. (Previously Presented) The system of claim 19, wherein the first data link is a proprietary data link.

21. (Previously Presented) The system of claim 19, further comprising a second data link that interfaces the proxy logic element.

22. (Previously Presented) The system of claim 21, wherein the gateway is further configured to transmit information responsive to the first message from the proxy logic element over the second data link.

23. (Previously Presented) The system of claim 21, wherein the gateway is further configured to receive a second message from the second data link and route, using the address map, the second message over the first data link to the source module.

24. (Previously Presented) The system of claim 23, wherein the second data link is a non-proprietary standard data link including one of J1939, CAN, MODBUS, serial standard data link, and the Ethernet.

25. (Previously Presented) The system of claim 24, wherein the gateway is further configured to translate the second message into a comparable message consistent with the first data link.

26. (Canceled).

27. (Previously Presented) A system for exchanging information in a work machine environment, the system comprising:

a network of modules coupled to a first data link included in a work machine;

a master controller remotely located with respect to the work machine and coupled to the work machine via a wireless data link, wherein the master controller is configured to control the modules; and

a gateway included in the work machine and configured to:

monitor the first data link for messages, wherein the messages are sent by the modules and intended for the master controller, intercept the messages from the first data link based on a determination that the messages are intended for the master controller, and

route the intercepted message, based on information in an address map, to proxy logic, wherein the proxy logic performs functions associated with the master controller.

28. (Currently Amended) A computer-readable medium including instructions for performing a method in a work machine environment, the method performed by a gateway and comprising:

monitoring a first data link for messages, wherein the messages are transmitted by source nodes and intended for destination modules;

determining whether a first message intended for a first destination module should be intercepted from the first data link based on a destination address included in the first message;

intercepting the first message when the gateway determines that the message should be intercepted; and

routing, based on information in an address map, the first message to a proxy logic element that performs functions associated with the first destination module based on data included in the first message.

29. (Currently Amended) A computer-readable medium including instructions for performing a method in a work machine environment, the method performed by a gateway and comprising:

monitoring a first data link connected to a plurality of modules, each module configured to direct messages to destination modules by adding to the messages an address identifier corresponding to the destination modules;

intercepting at least one of the messages based on a determination that the at least one message is intended for a destination module for which the gateway serves as a proxy; and

selectively providing, using an address map, the at least one message to program logic that performs, based on data included in the at least one message, work machine control functions similar to the destination module that may be connected to the first data link to perform the same functions.

30. (New) A system for processing messages in a work machine environment, comprising:

a first work machine including a first gateway; and

a second work machine including a second gateway and a destination module,

wherein the first gateway is configured to:

receive a first message having an identifier that identifies the destination module as a target for the first message,

determine, based on the identifier, whether to process the first message within the first gateway or to route the first message from the first gateway, wherein:

when the first gateway can process the first message, it performs functions similar to those of the destination module using data included in the first message, and

when the first gateway cannot process the first message, it routes the first message to the second gateway.

31. (New) The system of claim 30, wherein the second gateway is configured to:

determine, based on the identifier, whether to process the first message within the second gateway or to route the first message from the second gateway, wherein:

when the second gateway can process the first message, it performs functions similar to those of the destination module using data included in the first message, and

when the second gateway cannot process the first message, it routes the first message to the destination module.

32. (New) A method for providing proxy services in a work machine including modules interconnected by a data link and a gateway including first and second program logic, the method performed by the gateway comprising:

processing a message in the first program logic, wherein the message includes information identifying a destination module that is configured to perform an operation using data included in the message;

routing, based on an address map and the information included in the message, the message from the first program logic to the second program logic; and
performing, by the second program logic, the operation on the data included in the message.

33. (New) The method of claim 32, wherein processing the message in the first program logic includes at least one of:

generating the message by the first program logic; and
receiving by the first program logic the message from a source module.

34. (New) A gateway for providing proxy services in a work machine including modules interconnected by a data link, the gateway comprising:

first program logic configured to perform functions associated with at least a first one of the modules; and

second program logic configured to perform functions associated with at least a second one of the modules;

wherein the first program logic is configured to:

process a message, wherein the message includes information identifying a destination module that is configured to perform an operation using data included in the message, and

route, based on an address map and the information included in the message, the message from the first program logic to the second program logic, and

wherein the second program logic is configured to perform the operation on the data included in the message.

35. (New) The system of claim 34, wherein the first program logic is configured to at least one of:

generate the message; and

receive the message from a source module.